
Wood-Slide Oils

Overview: Interlube's Wood-Slide Oils are specially formulated lubricants for use in wood processing facilities. Designed to spray on wood as it is being formed to reduce wear on cutting/ molder tables, shaping/profiling equipment, routers, blades, planer beds, conveyor surfaces, and other metal and/or plastic surfaces caused by constant movement of heavy wooden pieces. It also reduces the potential for rusting and corrosion on those metal surfaces caused by the moisture and resins found in the wood.

The Wood-Slide Oils come in 2 formulations. The Wood-Slide Oil 33 is blended to quickly evaporate, leaving behind a trace oil film. The Wood-Slide Oil 32 evaporates much slower and leaves behind a heavier oil film providing extended component protection. Both products help to enhance material feed without chatter/ stick-slip. The fluid also improves the surface finish of the wood as it is being cut/ formed. These products contain no silicon so as to not affect painting of the finished wood surfaces. They also do not affect end processes of the wood pieces such as gluing, varnishing, or staining. The products are applied using either automatic lubrication units or with a manual spray gun. The amount applied is dependent on the type/ hardness of the wood being worked.

Operational Benefits: These products offer these competitive advantages to enhance your reliability:

- **Easy application** • **Excellent component protection** • **Moisture displacing** • **Low odor**
- **Rust/ corrosion protection** • **Silicone Free**

Application: Molder Bed Tables / Wood Profiling equipment

Typical Industries: These products are commonly used (but not exclusively) in the following industries: **Woodworking / Wood Forming**



Interlube Corporation

4646 Baker Avenue

Cincinnati, Ohio 45212-2594 USA

Tel: 513-531-1777 | Fax: 513-531-0193

SALES@INTERLUBECORPORATION.COM | WWW.INTERLUBECORPRATION.COM

International Manufacturer & Distributor of the World's Finest Lubricants & Cleaning Compounds

Wood-Slide Oils

Technical Properties

| Specification | Method | Wood-Slide Oil 32 | Wood-Slide Oil 33 |
|------------------------|----------------|-------------------------|--------------------------|
| Appearance | ASTM E 2680-16 | Clear, Light Amber | Clear, Light Amber |
| Specific Gravity | ASTM D 1298 | 0.81 | 0.79 |
| Flash Point (°F) | ASTM D 93 | >200 | >140 |
| Pour Point (°F) | ASTM D 97 | <-40 | <40 |
| Viscosity (cSt @ 40°C) | | 2.34 | 1.97 |
| Odor | | Minimal, Mild Petroleum | Minimal, Mineral Spirits |

The values shown are typical of current production. All of them may vary within tolerable ranges



Interlube Corporation
4646 Baker Avenue
Cincinnati, Ohio 45212-2594 USA
Tel: 513-531-1777 | Fax: 513-531-0193
SALES@INTERLUBECORPORATION.COM | WWW.INTERLUBECORPRATION.COM

05125