

CONFORMS TO TESTS  
SPECIFIED IN ASTM STP 332  
CONTAINS NO SILICONES OR  
CHLORINATED SOLVENTS  
SAFE ON PLASTICS, RUBBER  
AND PAINTED SURFACES

Features a forceful jet spray  
which helps provide rapid  
penetration through rust and  
corrosion to free frozen parts.

Contains Polytetrafluoroethyl-  
ene & Molybdenum Disulfide  
for added pressure and wear  
resistance.

Reduces friction and wear over  
a broad temperature range.

Leaves a long-lasting lubricat-  
ing film to defend against rust  
and corrosion.

#### DIRECTIONS:

Saturate part to be loosened  
and allow product to penetrate  
for a moment before attempting  
to break free. For heavily  
encrusted pieces a wire brush  
may be used to help remove  
corrosion. Apply a light final  
spray to all parts prior to  
reassembly.

NOTE: SPECIAL VALVE  
ALLOWS CAN TO BE  
SPRAYED WHILE HELD  
IN ANY POSITION

HMIS® RATING:	
HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

See Safety Data Sheet for  
complete safety information.

**CONTAINS NO OZONE  
DEPLETING CHEMICALS!**

MADE IN THE USA



# PENETRATING OIL

- **Frees Rusted Nuts – Bolts – Studs  
and Other Fittings**
- **Features a 360° Valve**
- **Fortified With PTFE and Moly**
- **Cleans Grease, Dirt, Dust and Sludge**
- **Helps Prevent Further Corrosion**



NET WT. 14 OZ (396 g)



**DANGER:** EXTREMELY FLAMMABLE  
HARMFUL OR FATAL IF SWALLOWED  
CONTENTS UNDER PRESSURE  
SEE OTHER CAUTIONS ON BACK PANEL



PENETRATING OIL



**DANGER:** Extremely flammable  
aerosol. Keep away from heat/  
sparks/open flames/hot surfaces.  
No smoking. Do not spray on an  
open flame or other ignition  
source. Pressurized container:  
Do not pierce or burn, even after  
use. Protect from sunlight. Do not  
expose to temperatures exceed-  
ing 49°C/120°F. Dispose of waste  
and residues in accordance with  
local authority requirements.

**FIRST AID: IF ON SKIN:** Wash  
hands after handling. **IF IN EYES:**  
Immediately flush eyes with  
plenty of water for at least 15  
minutes. Remove contact lenses,  
if present and easy to do. Get  
medical attention if irritation  
develops and persists. **IF  
INHALED:** Move to fresh air. Call a  
physician if symptoms develop or  
persist. **IF SWALLOWED:** Rinse  
mouth. Get medical attention if  
symptoms occur.

**CONTAINS:** Mineral Oil (8042-  
47-5), Petroleum Distillates  
(64742-46-7), Liquefied Petro-  
leum Gas (68476-86-8), Diethyl-  
ene Glycol Monobutyl Ether  
(112-34-52) and Mineral Spirits  
(64741-65-7).

Distributed by:  
**INTERLUBE CORPORATION**  
4646 Baker Avenue  
Cincinnati, Ohio 45212 USA  
Phone: (513) 531-1777  
Fax: (513) 531-0193  
[www.interlubecorp.com](http://www.interlubecorp.com)

Caution: Use only in a well  
ventilated area. Avoid contact with  
eyes and prolonged contact with  
skin. **KEEP OUT OF REACH OF  
CHILDREN.**